

# Filter-Table

 **Frequent use**

 **Full surface extraction**



## Applications

- Low to medium levels of smoke and dust
- Occasional to frequent use
- Welding and grinding

## Properties

- Spark separator
- Large, robust material support
- Activated charcoal filter (optional)

## Benefits

- Maintenance door allows easy filter change
- Effective spark protection ensures maximum safety
- Downdraft extraction throughout the whole working area
- Wide range of applications due to large working area of 1,200 x 800 mm

## Technical Data

Filter	
Filter stages	2
Filter method	Storage Filter
Filter surface	15.8 m <sup>2</sup>
Type of filter	Filter cassette
Filter material	Non-woven fibre
Filter class	F9
Additional filters	Pre-filter (aluminium)
Basic data	
Extraction capacity	1400 m <sup>3</sup> /h
Dimensions (w x h x t)	1200 x 800 x 1340 mm
Weight	153 kg
Motor power	1,5 kW
Power supply	3 x 400 V / 50 Hz
Rated current	3,2 A
Noise level	71 dB(A)
Additional information	
Fan type	Radial fan

## Order Data

Art. No.	Description
<b>950 400 001</b>	KEMPER Filter-Table

## Replacement Parts and Accessories

Art. No.	Description
<b>109 0010</b>	Main filter 15,8 m <sup>2</sup>
<b>109 0013</b>	Alu mesh Pre-filter insert
<b>109 0345</b>	Activated charcoal filter







**KEMPER**

Filter-Table