

Dusty

 For mobile use

 Manual filter cleaning



Applications

- Low to medium levels of smoke and dust
- Nozzles, funnel and torch extraction
- Repair work
- Alternating work places

Properties

- Manual filter cleaning
- Cleaning indicator
- KemTex® ePTFE filter cartridge
- Portable and mobile
- Two suction nozzles

Benefits

- For mobile use due to light weight
- Optimal adjustment to the welding process with stepless speed control

Accessories

- Suction hose
- Slot nozzle
- Funnel nozzle
- Connector for welding torches

Technical Data

Filter	
Filter stages	1
Filter method	Cleanable filter
Filter cleaning method	Manual
Filter surface	1.35 m ²
Type of filter	Filter cartridge
Filter material	ePTFE membrane
Filter efficiency	> 99.9 %
Dust classification	M
Basic data	
Extraction capacity	260 m ³ /h
Fan performance	340 m ³ /h
Dimensions (w x h x t)	300 x 360 x 641 mm
Weight	24 kg
Motor power	1,6 kW
Power supply	1 x 230 V / 50 Hz
Rated current	8.7 A
Noise level	74 dB(A)
Additional information	
Fan type	Suction turbine
Hose connection	Ø 2 x 45 mm

Order Data

Art. No.	Description
63 100	KEMPER Dusty

Replacement Parts and Accessories

Art. No.	Description
109 0432	1,35 m ² spare filter with KemTex® ePTFE membrane
232 0010	Funnel nozzle flexible, with magnetic foot
106 0071	Adaptor for welding torches with integrated extraction 42 - 44 mm
106 0084	Adaptor for welding torches with integrated extraction 30 - 38 mm
106 0104	Adaptor for welding torches with integrated extraction 39 - 42 mm
232 0008	300 mm, with magnetic foot
232 0009	Slit nozzle, 600 mm, with magnetic foot
93 070 004	High vacuum hose Ø 45 mm, 2.5 m long
93 070 005	High vacuum hose Ø 45 mm, 5.0 m long
93 070 006	High vacuum hose Ø 45 mm, 10.0 m long



KEMPER
Dusty

